

Tray sealer (PREMIUM 2000)

Product description

- Machine adapted to shrink film
- Automatic and motorized film unwind
- Automatic and motorized excess film wind
- External vacuum pump
- Threshold control for vacuum and gas pressure
- Stainless steel casing and treated aluminium tools
- Standard electrical, pneumatic and mechanical components adapted to the food industry



Product general characteristics

- Instantaneous format change
- Automatic preheating
- 4 « ready to use tools »
- Integral storage for ultra-light tools
- Machine / operator interface with user friendly screen
- Robust and compact
- Ergonomically designed for security and productivity

Technical product characteristics

- Machine size (l x w x h in mm) : **2500 x 900 x 1600**
- Maximum tray size (in mm) : **390 x 270 x 90**
- Maximum width of sealing film (in mm) : **440**
- Rate with vacuum and gas (cycles / minute) : **1 à 12**
- Electrical connection (50 Hz – 60 Hz) : **400 V Three-phase – Neutral – Earth**
- Compressed air supply : **8 constant bars**
- Gas supply : **6 bars**
- Instantaneous format change : **Automatic**
- Loading and recovering of trays : **During the sealing cycle**
- Tray feed and advance of the trays on input conveyor : **Automatic**

GUELT.

Options availables

- Oxygen vacuum pump
- Remote diagnostic maintenance (equipment and access)
- Fully adaptable for your weighing-labelling system : straight or loop conveyors
- Premium Pack:
 - - 4 tray sizes: 1523 - 1825 - 2130 - 2734 (maximum height 90 mm)
 - - Unique film width
 - - Set-up / staff training / production assistance / control visit after 1 month of production / access to remote diagnostic maintenance (excluding equipment)

GUELT.

ZI KERVIDANOU 1 - 29300 QUIMPERLE
TEL : +33 (0)2 98 96 38 38 - WWW.GUELT.COM
EMAIL : GUEL@GUEL.COM