



Bolphane[®] BTS

High sealing performance shrinkfilm

- **Excellent heatsealing characteristics.**
- **Secure package at low temperatures.**
- **Good optics.**
- **Toughness improving machinability.**

APPLICATIONS

→ Bolphane BTS belongs to the range of specialized films dedicated to high speed HFFS machines.



→ Excellent sealing characteristics, superior optics, resisting at low temperatures make BTS perform in packaging frozen food products such as pizzas.

Bolloré

Bolphane[®] BTS

SEALING PERFORMANCE

- The unique combination of rigid layers at the core and sealable external layers means high performance in sealing at high speed.



TECHNICAL FEATURES

→ PROPERTIES	13 MICRONS	15 MICRONS	18 MICRONS
Gloss (85°angle) in %	117	116	115
Haze (%)	2		
Shrinkage (%) at 120°C	30		
Length of the roll (m)	3 100	2 670	2 250
Internal diameter (mm)	76,2		
External diameter (mm)	245		

PRESENTATION

- Bolphane BTS exists in Singlewound (BTS-S) only. For any specific request, please refer to the commercial documentation.

→ VERSION	WIDTH (mm)		
	mini	maxi	increment
BTS-S	300	750	10

○ The technical features of the products defined herein are given as typical values. They are guides for the use of the quoted films values and are not for use as limiting specification. Users have to check-up that they are suitable with all the applications as performance may vary with processing conditions. Properties and performance are subject to change and BOLLORÉ keeps the right to modify the definition and properties of its products without prior notice.

Bolloré